

**لیست DVR 3MP H.264**

شہر یور ۱۳۹۶



Item		3MP AHD / TVI / CVI / 960H / IP Hybrid DVR (w/ sensor alarm)			3MP TVI / AHD / CVI / 960H / IP Hybrid DVR		
Model		SN-DVR4MM	SN-DVR8MM	SN-DVR16MM	SN-DVR32MM		
picture							
Video Input Format		AHD (up to 3MP), TVI & CVI (up to 1080P), 960H, IP			TVI (up to 3MP), AHD & CVI (up to 1080P), 960H, IP		
Video & Audio	Video Input	BNC	4 inputs	8 inputs	16 inputs	32 inputs	
		BNC & IP	Up to 6 Channels (BNC x4 + IP x2)	Up to 12 Channels (BNC x8 + IP x4)	Up to 24 Channels (BNC x16 + IP x8)	Up to 40 Channels (BNC x32 + IP x8)	
		IP Only	6 inputs	12 inputs	24 inputs	8 inputs	
	Video Output		1 VGA(up to 1080P) and 1 HDMI(4CH & 8CH 1080P, 16CH up to 4K) output			1ch VGA, 1ch HDMI	
	Audio input / output (RCA)		4 inputs / 1 output	8 inputs / 1 output	16 inputs / 1 output	4 inputs / 1 output	
Recording	Analog	3MP	9fps (AHD Only)	7fps (AHD Only)	12fps (AHD Only)	8fps (TVI Only)	
		2MP(1080P)	PAL/NTSC: 15fps			PAL/NTSC: 15fps	
		1MP(720P)	PAL: 25fps / NTSC: 30fps			PAL: 25fps / NTSC: 30fps	
		960H	PAL: 25fps / NTC: 30fps			PAL: 25fps / NTSC: 30fps	
	IP	IP Camera Support		4MP / 3MP / 2MP(1080P) / 1M(720P) / 960H			4MP / 3MP / 2MP(1080P) / 1M(720P) / 960H
		Recoding Frame Rate		(Per Channel) PAL:25fps NTSC: 30fps			(Per Channel) PAL:25fps NTSC: 30fps
		Input Bandwidth		8Mbps~24Mbps	16Mbps~48Mbps	32Mbps~96Mbps	32Mbps
		Max. Output Bandwidth		32Mbps	32Mbps	64Mbps	128Mbps
		Peak Decode Performance		2CHs realtime @1080P	4CHs realtime @1080P	8CHs realtime @1080P	16CHs realtime @1080P
	Recording Mode		Continuous / Manual / Schedule / Motion Detection / Sensor Triggered				
HDD Supported		1 SATA HDD, up to 6TB		2 SATA HDDs, up to 12TB	4 SATA HDDs, up to 24TB		
Network	Network Interface		RJ45, 10M/100M			RJ45, 10M/100M	
	Network Type		Static IP, DHCP, PPPoE, 3G			Static IP, DHCP, PPPoE, 3G	
	Web Surveillance Support		IE / Firefox / Google Chrome / Mac Safari				
	Mobile App Support		iOS & Android APP: RxCamView, support to live view max. 80 channels			iOS & Android APP: RxCamView	
Playback & Backup	Local Playback Simultaneously		Max. 4 Channels	Max. 8 Channels	Max. 16 Channels	Max. 16 Channels	
	Remote Playback via Network		Max. 4 Channels Simultaneously via CMS, IE/Mac Safari or Mobile App				
	Backup Method		USB, Network				
	Backup Method		USB, Network, e-SATA (Optional)				
General	USB		USB2.0 x2			USB2.0 x2	
	PTZ Control		Yes, built-in RS485 & Coaxial Protocol (UTC)			Yes, built-in RS485 & Coaxial Protocol (UTC)	
	Sensor & Alarm Port		N/A	8 inputs / 1 output	16 inputs / 1 output	8 inputs / 1 output	
	Power Supply		DC 12V/2A		DC 12V/5A	DC 12V/5A	
	Dimension(WxDxH)		300 x 227 x 53mm		378 x 340 x 50mm	378 x 326 x 66mm	
	Working Environment		-10°C~+55°C / 10%~90%RH				-10°C~+55°C / 10%~90%RH